



# DAMPLOCK<sup>®</sup>

## MASONRY WATERPROOFING PAINT

PRODUCT  
DATA SHEET

**DESCRIPTION:** Water-based acrylic paint for waterproofing interior basement walls and exterior masonry; low odor and low VOC.

**Typical Uses:**

- ✓ Basement walls
- ✓ Above & Below Grade
- ✓ Bird baths & pre-cast fixture
- ✓ Brick & Stucco walls
- ✓ Retaining walls
- ✓ Foundations
- ✓ Concrete & Cinder Blocks

**Important:** Read all directions thoroughly. Recommended: Wear gloves and safety glasses.

**SURFACE PREP\*:** New concrete must have cured for a minimum of 30 days. The surface should be clean, sound and free of dirt, dust, oil, wax and grease. DampLock may be used on painted surfaces to improve water resistance; however, surface must be bare concrete for waterproofing

**Cleaning:** Remove mold/mildew with a solution of 1 part bleach, 3 parts water. Rinse and let dry. Remove efflorescence with a wire brush and solution of 1 part muriatic acid, 9 parts water. Neutralize acid with a solution of baking soda and water (i.e., 1 lb. baking soda, 5 gallons of water). Rinse thoroughly: let dry.

**Repairs:** Repair surface breaks around wall/floor joints and patch cracks with fast-setting hydraulic cement or concrete crack filler, using trowel to smooth patch to surrounding area.

**APPLICATION:** Read "LIMITATIONS" section before use. Ready-to-use; do not dilute. Stir thoroughly before (and occasionally during) use. DampLock may be applied to a damp surface; however, application to a dry surface provides best results. Apply first coat with a 1/2" to 3/4" nap roller cover or high quality, nylon-polyester brush. Use a brush to work paint into the grout lines. Allow to dry 3 hours, then apply second coat. 2 coats are recommended for waterproofing and are required for a warranty claims.

**Note:** If leak occurs after applying 2 coats, pin holes may be present. Paint these areas again, using a brush to work paint into the pores.

**COVERAGE:** 75–125 sq.ft. per gallon, depending on surface porosity. Second coat coverage is approximately 50% greater.

**DRY TIME:** Dries in 2–3 hours, depending on temperature and humidity.

**TINT LIMITS:** Up to 4 oz. colorant per gallon.

**PAINTING:** Wait 24 hours before topcoating with latex/acrylic paint.

**CLEAN-UP & STORAGE:** Clean tools immediately after use with soap and water. KEEP FROM FREEZING.

**LIMITATIONS:** Use only when air and surface temperatures are 55° to 90°F (13° to 32°C). Do not apply if rain is forecast within 24 hours. Do not use on horizontal surfaces.

\*Sanding or removing paint containing lead may be hazardous. For information contact the National Lead Information Center at 1-800-424-LEAD or [www.epa.gov/lead](http://www.epa.gov/lead).

**CAUTION: KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.** May cause eye and skin irritation. Avoid breathing vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after use.

**FIRST AID: Eye Contact:** Flush thoroughly with water for at least 15 minutes. If irritation persists get medical attention. **If Inhaled:** If affected by vapors or spray mist, move to fresh air. If breathing difficulty continues get medical attention. **If Swallowed:** Drink 2 glasses of water. Get immediate medical attention.

**15 YEAR WARRANTY  
STOPS UP TO 15 PSI**



Product	No.	Unit	UPC Code	Carton Bar Code	Carton Size ( W x D x H )	Cube / Wt. ( cubic ft / lbs )	Carton Qty	Pallet Qty
DampLock Masonry Waterproofing Paint	131001	1 gallon	0 15944 13101 7	1 00 15944 13101 4	14.38 x 14.38 x 8.5	1.02 / 52.53	4	45
DampLock Masonry Waterproofing Paint	131005	5 gallon	0 15944 13105 5	–	–	1.35 / 63.72	1	36



# DAMPLOCK®

## MASONRY WATERPROOFING PAINT

- SUPERIOR DURABILITY
- INTERIOR/EXTERIOR USE
- FOR COATED & UNCOATED VERTICAL SURFACES

### TECHNICAL INFORMATION

- Meets waterproofing standards for below grade masonry: TT-P-1411A / ASTM D7088-4 hydrostatic pressure
- Stops up to 15 PSI water pressure
- Mildew resistance: ASTM D5590-00 rated excellent
- Strong alkali resistance
- Resists efflorescence
- Complies with California air pollution regulations
- Reduces radon gas penetration
- Interior / exterior use
- Satin finish
- Premium acrylic formula
- Brush / roller application
- Water-based
- Ultra low odor
- Bright white
- VOC < 100 g/L – EPA Method 24 – Waterproofing Sealer Category
- OTC-compliant

**FOR BASEMENTS, RETAINING WALLS & FOUNDATIONS**

**RESISTS MOLD & MILDEW GROWTH**

**ULTRA LOW ODOR, READY-TO-USE**

**PAINTABLE**



**\*LIMITED 15 YEAR WATERPROOFING WARRANTY:** A limited 15 year warranty is available on the quality and performance of this product on a per job basis. Contact our technical service dept. for details on this warranty program prior to painting. Otherwise, manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of SEAL-KRETE product or refund of purchase price. Convenience Products will not be responsible for labor or the cost of labor for removal or application of any product.

**TECHNICAL SUPPORT:** For more information on surface prep or application guidelines, or to obtain a Material Safety Data Sheet, call 1-800-323-7357, M-F (8:00 am–5:00 pm EST) or visit our website at [www.seal-krete.com](http://www.seal-krete.com).