



# TINTABLE FLOOR-TEX®

## DECORATIVE TEXTURE COATING

PRODUCT DATA



VOCs Less than 50 grams/liter

**SEAL-KRETE® Floor-Tex®** is a durable, non-slip, texture coating that provides a decorative finish for concrete and masonry surfaces such as pool decks, patios, porches, ramps and walkways. Paintable and tintable, this premium acrylic formula hides surface imperfections while providing a tough finish that resists damage from moisture, salt, oil, gas and chlorine. Performance-tested on commercial traffic sites, Floor-Tex outwears conventional anti-skid coatings, paints and stains. It's also suitable for wood stairs. **Important:** Read all directions thoroughly. Always wear gloves and eye protection.

**SURFACE PREP:** NOTE: Proper surface prep is critical to product performance. The surface should be clean, dry, sound and free of dirt, dust, oil, wax and grease.

**Oil Stains:** You may need to use a heavy duty degreaser to lift stubborn stains.

**Bare Concrete:** Concrete must have cured for a minimum of 30 days before application. Etch surface with SEAL-KRETE Clean-N-Etch to allow for proper penetration and adhesion. Etching is especially important for smooth-troweled concrete surfaces (like carport and garage floors) and is also recommended for rough finished surfaces. After etching, rinse thoroughly and let dry. For best results, apply one thin coat of SEAL-KRETE Lock-Down Epoxy Bonding Floor Primer.

**Surface Cracks:** Use a paintable acrylic or urethane caulk to repair hairline cracks. For other cracks (up to 3/8" wide), use a flexible, acrylic concrete patch or filler. Let all materials cure fully.

**Previously Stained or Painted Concrete:** Remove loose or peeling paint and degloss surface by sanding (150-200 grit sandpaper).\* Follow with a general cleaning. Rinse thoroughly and let dry. Then coat the surface with SEAL-KRETE Lock-Down Epoxy Bonding Floor Primer.

**APPLICATION:** Read "LIMITATIONS" section before use. A minimum of 2 coats is recommended. Apply first coat and let dry to touch, then apply second coat in a direction perpendicular to the first.

**Brush:** Use a high quality, nylon bristle brush.

**Roller:** Use a short nap (3/16") cover – synthetic or mohair blend.

**Sprayer:** Use Floor-Tex PROFORMANCE for spray application or decorative stenciling.

**TINT LIMITS:** Up to 4 oz. colorant per gal. white base; up to 5 oz. colorant per gal. deep base.

**TOPCOATING:** To finish the system and for easier maintenance, wait 24 hours before applying one thin coat of SEAL-KRETE Clear-Seal sealer.

**COVERAGE:** 1 gallon covers approx. 120 sq. ft. (60 sq. ft./2 coats), 5 gallons covers approx. 600 sq. ft. (300 sq. ft./2 coats), depending on substrate and thickness applied.

**DRY TIME:** Dry to touch in 1-4 hours. Dry to foot traffic in 24 hours. Will accept vehicular traffic in 3-5 days. **Note:** Dry times vary depending on temperature and humidity.

**CLEAN-UP & STORAGE:** Clean all tools immediately after use with soap and water. Store unused product in a dry place above 32°F.

**MAINTENANCE:** Clean occasionally with a mild soap and water solution. Do not use solvent, citrus or oil-based cleaners. If needed, scrub surface with a soft bristle brush or shop broom. Rinse with a garden hose or power washer (less than 1200 psi) held at least 18 inches from the surface, using a fan spray pattern. Re-apply sealer every 2 years, or as needed.

**LIMITATIONS:** Do not apply if rain is expected within 24 hours or if temperatures fall below 50°F within 24 hours of application. Do not apply below grade. Do not use on basement walls or in areas subject to hydrostatic pressure or standing water. Do not apply to concrete that has not fully cured.

**CAUTION: EYE IRRITANT.**

Contains Dipropylene Glycol N-Propyl Ether. Avoid contact with eyes and prolonged contact with skin. Do not ingest.

**FIRST AID:** In case of eye contact, flush with water for 15 minutes. If irritation persists, get medical attention. In case of skin contact, wash thoroughly with soap and water. If swallowed, drink 1-2 glasses of water and immediately contact medical services regarding any instructions to induce vomiting.

**KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



Product	No.	Unit	UPC Code	Carton Bar Code	Carton Size (L x W x H)	Carton Size (cubic ft / lbs)	Carton Qty	Pallet Qty
White Base	460001	1 gallon	0 15944 46001 8	1 00 15944 46001 5	14 x 14 x 8	1.03 / 50	4	45
White Base	460005	5 gallon	0 15944 46005 6	—	—	N/A / 60	4	36
Deep Base	470001	1 gallon	0 15944 47001 7	1 00 15944 47001 4	14 x 14 x 8	1.03 / 49	4	45
Deep Base	470005	5 gallon	0 15944 47005 5	—	—	N/A / 59	4	36



**For PATIOS, POOL DECKS, STAIRS, RAMPS, PORCHES, WALKWAYS & MORE DURABLE, NON-SLIP COATING • HIDES IMPERFECTIONS • OIL, SALT & CHLORINE RESISTANT**

**TECHNICAL INFORMATION**

- Solids: 60%
- Acrylic Resin: Proprietary
- Water-based
- Odor: Low
- Clean-up: Soap and water
- Shelf Life: > 2 years (closed container)
- ASTM G-23 UV-resistance: 1200 hours
- E-84 Flame Spread: Pass
- C355-64 Water Vapor Transmission: 10.9 perms
- D412-75 Tensile Strength: 2239 psi,  
50% Elongation
- D 5590-00 Mildew Resistance: Excellent
- D2241 Abrasion Resistance: .0195 grams lost
- D1308 Chemical Resistance:
  - Water-resistant
  - Gas-resistant
  - Oil-resistant
  - Salt-resistant
  - Chlorine-resistant

**Limited Warranty:** Manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price. Convenience Products will not be responsible for labor or the cost of labor for removal or application of any product.

**Technical Support:** For more information on surface prep or application guidelines, or to obtain a Material Safety Data Sheet, call 1-800-323-7357, M-F (8:00 am - 5:00 pm EST) or visit our website at [www.seal-krete.com](http://www.seal-krete.com).

Give new life to patios, driveways, walkways, porches, steps and more with Floor-Tex decorative texture coating. It hides imperfections while providing a beautiful decorative surface that can be tinted to match your home decor!



Create a Pattern with Stencils



- Meets ADA Requirements for Non-slip Surfaces
- Premium, Water-based Acrylic
- Easy Brush / Roller Application
- Self-priming
- Paintable / Tintable
- Interior / Exterior Use
- Low VOCs < 50 g/L

Great for Pool Decks – Barefoot Friendly



\*Sanding or removing paint containing lead may be hazardous. For information contact the National Lead Information Center at 1-800-424-LEAD or [www.epa.gov/lead](http://www.epa.gov/lead).

