



# FLOOR-TEX<sup>™</sup> PROFORMANCE

PRODUCT DATA

ACRYLIC, NON-SLIP TEXTURED COATING (Spray/Trowel Formula)

**IMPORTANT:** Read all directions thoroughly. Always wear gloves and eye protection.

**BASIC USE:** Floor-Tex PROFORMANCE is a decorative, non-slip coating for long-term protection and beautification of concrete and masonry surfaces. PROFORMANCE is spray/trowel applied on interior or exterior horizontal, high-traffic surfaces including walkways, patios, stairs, pool decks, balconies, ramps, driveways and carports. For other surface compatibility or vertical applications, contact the SEAL-KRETE technical department.

**SURFACE PREPARATION:** Do not apply over painted or stained concrete surfaces. The surface should be bare, clean and oil-free. To remove oil stains, use a degreaser or SEAL-KRETE OSR (oil stain remover). Make sure all curing compounds and releasing agents have been removed. Repair all cracks and surface breaks. Cover windows, doors, etc. prior to application. Use caution when applying on windy days. Immediately remove any overspray with water. Do not apply to concrete that has not fully cured (at least 30 days). For new or smooth concrete, acid etching and neutralization are required for proper adhesion. Use a 1:3 solution of muriatic acid and water or SEAL-KRETE Clean-N-Etch and follow manufacturer's directions. For complete acid-etching procedures, including surface neutralization, visit our web site at seal-krete.com. For superior adhesion, prime the surface with 1 coat of SEAL-KRETE Waterproofing Sealer and let dry.

**APPLICATION & EQUIPMENT:** Note: Use exterior paints only. Add the desired color of exterior gloss, semi-gloss, satin acrylic latex, acrylic floor enamel or industrial acrylic enamel paint at a ratio of 1 gallon to a 45 lb. pail of PROFORMANCE. Mix well with a mechanical mixer. PROFORMANCE will take on the same color as the paint (light colors may darken slightly). PROFORMANCE may be applied by trowel, spray hopper or larger recommended texture sprayer. A test application should be made to a small area of surface to determine product suitability and desired appearance. Wait 24 hours before allowing light foot traffic, 72 hours for vehicular traffic.

**FINISH TYPE:**

**Spray Finish:** Spray with a hopper gun or texture sprayer (call SEAL-KRETE for recommendation) at 1/16" thickness. Hold spray nozzle approximately 12-15 inches from surface when spraying. When using a hopper gun, the orifice should be set on 1/4" or 4mm. Orifice can be adjusted 6 or 8mm to obtain desired texture. Set air pressure to approximately 20-30 psi.

**Trowel Finish:** Trowel at 1/16" thickness.

**Skip Trowel (knockdown finish):** Spray or trowel first coat at approximately 1/16" thickness. Allow to dry a minimum of 6 hours at 72°F. Then apply splatter coat with a hopper gun. Pressure should be approximately 2-5 psi and orifice should be set at 5/16" or 8mm. Trowel down to desired knockdown aesthetics. Unlevel and rough surfaces may require 2 coats prior to knockdown.

**Stencil Pattern (brick, herringbone, basket weave, logos, etc.):** Spray or trowel base coat at approximately 1/16" thickness. Allow to dry a minimum of 6 hours at 72°F, then lay stencil over base coat and spray second coat of PROFORMANCE at approximately 1/16"

thickness. While still wet, carefully remove stencil. (If a paper stencil was used, let coating dry fully [8-24 hours] before removing.) Sweep up residue.

**FINISH COAT:** After PROFORMANCE has dried for 24 hours, apply a coat of SEAL-KRETE Floor-Tex Topcoat Sealer to add a gloss finish, improve cleanability and increase durability of the textured coating. Follow sealer application directions.

**COVERAGE:** Coverage varies depending on the substrate and thickness applied. Rough, textured or unlevel surfaces may require 2 coats; each applied at approximately 1/16" thickness. With paint added, a 45 lb. pail of PROFORMANCE will cover approximately 200 sq.ft.

**DRY TIME:** Dry to recoat in 6 hours. Dry to foot traffic in 24 hours. Will accept vehicular traffic in 72 hours.

**MAINTENANCE:** Wait 30 days before initial cleaning. Clean with a mild soap and water solution and a soft bristle shop broom to remove dirt, salt and oil from film surface. Do not use solvent based cleaners. Do not clean using a pressure washer.

**LIMITATIONS:** Do not apply outside if rain is forecast within 24 hours of application. Do not apply if air, substrate or product temperature is less than 50°F. Temperature must remain above 50°F for 24 hours after application. Do not add oil/alkyd based paint, interior latex paint or flat exterior latex paint. PROFORMANCE softens when in contact with some solvents such as acetone, xylene, toluene and gasoline – but will recover once solvent evaporates. Do not use in areas subject to hydrostatic pressure, constant standing water (inside swimming pools, ponds, water holding tanks, water treatment tanks, etc.) constant washing areas (car washes, showers) or on basement walls. Allow new concrete patch areas to cure 7 days before applying PROFORMANCE. Allow extra drying time for interior applications and high humidity environments. Do not apply with brush, roller or broom. Each coat should be a maximum of 1/8" thick. Coating must be free of "through the film" pinholes. Dry powder from overspray must be removed from surface while continuing spray application.



| PRODUCT NUMBER | UNIT SIZE | UPC CODE        | CARTON QTY | CARTON CODE | CARTON SIZE (L X W X H) | CARTON SIZE (CUBIC FEET) | CARTON WT. (LBS) | PALLET QTY. (CARTONS) |
|----------------|-----------|-----------------|------------|-------------|-------------------------|--------------------------|------------------|-----------------------|
| 400003         | 45 lb.    | 0 15944 40050 2 | 1          | NA          | 12 X 12 X 15            | 1.25                     | 48               | 36                    |



PROVIDES DURABLE UNIFORM COATING • HIDES IMPERFECTIONS, STAINS & DISCOLORATIONS  
DECORATIVE FINISH • EASY SPRAY APPLICATION – IDEAL FOR USE WITH STENCILS

# FLOOR-TEX™ **PROFORMANCE**

Professional Spray/Trowel Formula



Meets or Exceeds:

ASTM D-1308 for chemical resistance

ASTM D-4060 for abrasion resistance

ASTM D-4541 for surface adhesion

ASTM F-1677 for skid-resistance

**CLEAN-UP & STORAGE:** Clean all application tools with soap and water immediately after use. Store unused product in a dry place at room temperature (above 32°F). Do not freeze.

**TECHNICAL SUPPORT:** For more information, technical assistance or to obtain a Material Safety Data Sheet, visit our website or call 1-800-323-7357, M-F 8 am-5 pm.

**CAUTION: KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:** *For Eye Contact:* Flush with water for 15 minutes. *For Skin Contact:* Prolonged contact may cause irritation. Wash affected area with soap and water. *Inhalation:* If headache or nausea is experienced, remove the individual to fresh air. If symptoms persist, seek medical attention. *If Swallowed:* Induce vomiting and seek immediate medical attention.

**WARRANTY:** Manufacturer/seller makes no warranty of any kind, except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.

## LIQUID PROPERTIES

Solids: 70% Non-Volatile

Acrylic Resin: Proprietary

Water Based

Odor: Low

Appearance Wet: Neutral

Appearance Dry: Various Colors

Clean-Up: Soap and Water

Shelf Life: >2 Years (closed container)

- For walkways, patios, stairs, pool decks, balconies, driveways, carports, ramps
- Mix with any color exterior gloss or latex floor enamel
- Ideal for use with stencils
- Water based
- Non-Cementitious
- Interior/Exterior

